

Datasheet

COMfortel® 600



Attractively designed, versatile analogue phone with contrasting display and speed dialling keys



- Calling number and name display (CLIP and CNIP) if registered in the local and the central phone book of the PBX
- 99 phone book entries with name
- 10 programmable abbreviated dialling keys
- Separate interface for not cordless headsets
- Speakerphone mode

Your advantages in detail

Even the entry-level model in our COMfortel series has a cross-shaped touch pad to help you navigate through the menu. Together with the adjustable housing feet, which set the phone's angle, this makes everyday use (for example, as an extension to a PBX) more convenient. The option to mount the phone on a wall is particularly useful in hotels, workshops and industrial settings.

When connected to an analogue extension connection, the COMfortel 600 has a multitude of useful functions to make telephoning more convenient: Every telephone number stored in the local or central tele-

phone book is shown clearly on the three line LC display, along with the relevant name. The crystal-clear sound quality brings your call partner within arm's reach, no matter whether you're making an analogue call with a receiver, in hands-free operation or with a COMfortel H-100 headset.

Although the COMfortel 600 is ideally suited for use as an extension to our PBXs, it is equally at home on a/b ports on PBXs from other manufacturers or even when connected directly to analogue exchange line connections.

do you speak
FONtevo®

Features at a glance

SYSTEM FUNCTIONS

- 10 programmable abbreviated dialling keys
- Ringtone, handset and hands-free speaker volume adjustable
- Calling number and name display (CLIP/CNIP) if registered in the local and the central phone book of the proprietary ICT system
- Microphone mute
- Phone book, 99 entries with name
- Power supply via the system connection, no external power supply or batteries required
- Set-up angle adjustable in 3 steps
- Desktop and wall mounting

COMPATIBLE PRODUCTS

- 16118 / COMpact 4000
- 16119 / COMpact 4000 UK
- 16334 / COMpact 5200
- 16335 / COMpact 5200R
- 16336 / COMpact 5500R
- 16339 / COMpact 5500R UK
- 16670 / COMmander® 6000
- 16671 / COMmander® 6000R
- 16672 / COMmander® 6000RX
- 16347 / COMfortel® H-200

TECHNICAL SPECIFICATIONS

- Power supply: via the analogue port
- Power consumption: 0.8 W max.
- System connection: analogue port
- Headset: separate interface for corded speaker/microphone sets
- Operating elements: dialing keys with vanity code, 13 function keys, 10 programmable function keys
- Display: alphanumeric display, 3 lines, monochrome
- LEDs: 4, red
- Handset: wideband audio, electret-microphone, dynamical loudspeaker, hearing aid compatible
- Hook switch: magnetically switching contact
- Loudspeaker: 8 Ohm, Ø 52 mm
- Case: plastic
- Colour: black
- Dimensions (w x h x d): 223 mm x 148/158/168 mm x 185 mm
- Weight: approx. 940 g
- Compliance: CE

DELIVERY

- Basic unit
- Handset (receiver) with connection cable
- Connection cable RJ-11/RJ-11 (length approx. 3 m)
- Adapter TAE-F/RJ-11
- Operating Manual (German/English)

ORDERING INFORMATION

Designation: COMfortel® 600

Article number: 90064