

COMfortel® M-725



Compact, well-designed and even more powerful



- Modern design – large 2.4" TFT-colour display with intuitive user interface
- Scratch and disinfectant resistant
- Support for alarm, messaging and location (ALM)
- AAA batteries in accordance with the requirements of the EU Ecodesign Directive
- Headset operation via Bluetooth 5.1 or 3,5 mm phone jack

Your advantages in detail

Even at first glance, the COMfortel M-725 impresses with its elegant appearance and handy design. It is the smallest and lightest DECT terminal in the Auerswald portfolio. It is ideally equipped for everyday business use with a long talk time, brilliant voice quality, vibration alarm and audio profiles. This allows it to be quickly and optimally adapted to your personal requirements in any situation. The range of functions is rounded off by Bluetooth 5.1 and a practical USB-C interface.

Administrators will also be delighted. Automatic configuration and updates make their lives easier and maintenance more effective.

With its smooth surface made of high-quality polymer, the handset is scratch-resistant and resistant to disinfectants, making it suitable for use in a wide range of applications.

Optimal integration into the alarm functions of the COMfortel DECT system with alarm signals and icons make the COMfortel M-725 suitable for workplaces with special requirements. For this purpose, the handset now also has an easy-to-use alarm button on the top of the device.

Features at a glance

USER INTERFACE

- Illuminated, graphical 2.4" TFT colour display, 240 x 320 pixels, up to 8 lines and 65,000 colours
- Intuitive, modern user interface with icons, display keys, five way navigation key and function keys

AUDIO FEATURES

- HD audio supporting HDSP™/CAT-iq 2.1
- 32 selectable ringer melodies with 5 volume levels and crescendo
- Vibration alarm
- Selectable audio profile
- Headset via Bluetooth® or 3.5 mm jack

KEYPAD

- Illuminated, scratch and disinfectant resistant
- Message waiting key with blinking LED
- Profile key to apply personal, silent and loud settings directly
- Keylock (#-key) with PIN protection
- Special function key, at the top of the handset, e.g. for direct dialing or alarm

ALARM FEATURES

- Alarm, Messaging, Location (AML) support: Alarm call is sent via MQTT protocol or via a call to the alarm server
- Alarm key (top of the handset)
- 21 message icons in 5 colours
- Bluetooth/BLE: Bluetooth beacon and beacon scan to locate the position in case of emergency

INTERFACES

- DECT
- Bluetooth® for headset (hands free and headset profile) and for data exchange / firmware update
- vCard exchange with compatible mobile phones
- USB-C for charging function and data exchange / firmware update
- Headset connector 3.5 mm

ACCESSORIES

- Professional belt clip (optional)
- Snap-in for Multicharger

NOTE

- The correct placement of the radio cells is decisive for the smooth functioning of your IP-DECT system; we therefore recommend that you leave the dimensioning and configuration to a qualified specialist dealer
- A DECT measurement can be used to determine exactly where, for example, a further basis is required to ensure supply

COMPATIBLE PRODUCTS

- 90686 / COMfortel® WS-500S
- 90687 / COMfortel® WS-500M
- 16118 / COMpact 4000
- 16334 / COMpact 5200
- 16335 / COMpact 5200R
- 16336 / COMpact 5500R
- 16670 / COMmander® 6000
- 16671 / COMmander® 6000R
- 16672 / COMmander® 6000RX
- 16023 / COMtrexx® Advanced
- 16022 / COMtrexx® Business
- 90027 / COMtrexx® Next
- 90024 / COMtrexx® Flex
- 16021 / COMtrexx® VM

TECHNICAL SPECIFICATIONS

- Display: illuminated, graphical TFT colour display (2.4", 240 x 320 pixels, 65,000 colours)
- Radio interface: DECT/GAP, 1880-1900 MHz
- Typical range: 300 m outdoors, 50 m indoors
- Power supply: 2 batteries (NiMH) 1.2 V, 1,500 mAh max.
- Talk time: up to 12 hours
- Standby time: up to 320 hours
- Fast charge: 80 % after 2,5 h
- Case: plastic
- Colour: Dark Titanium
- Dimensions (w x h x d): 52 mm x 133 mm x 22 mm
- Weight Handset: approx. 114 g, incl. batteries
- Operating temperature: between +5 °C and +45 °C
- Storage temperature: between -15 °C and +60 °C
- Relative humidity: between 20 % and 75 %, non condensing
- Compliance: CE

DELIVERY

- Handset
- Battery cover
- 2 batteries (NiMH), type AAA
- Belt clip
- Charger
- Power adapter for charger
- Manual and security leaflet

ORDERING INFORMATION

Designation: [COMfortel® M-725](#)

Article number: [90246](#)

EAN Code: [4019377902462](#)