

## COMfortel® 1400

ISDN system phone for first-time customers with 3.5" TFT touch display and optional answering machine.

- 3.5" colour display with touch function
- Automatic detection of S<sub>0</sub> or U<sub>P0</sub> connection
- Optimal acoustic properties
- Local telephone book with 1600 entries
- Programmable function keys for engaged, direct dialling and system functions
- Power supply via system connection – no separate power supply required
- Angle of inclination adjustable in 3 steps
- Desktop and wall mounting
- Customizable language



Discover a new dimension of operating convenience: the COMfortel 1400 features a colourful 3.5" touch display which ensures extremely quick access to all the main functions. It automatically recognises whether your PBX system has an S<sub>0</sub> port or a U<sub>P0</sub> port which means you can use its multiple talents right away! E.g. the integrated phonebook which accommodates up to 1600 entries or the ten programmable keys (on two levels) for engaged, destination dialling and system functions.

Benefit from superior acoustic properties – whether talking or listening to the optional answering machine. The latter operates with uncompressed recordings for perfect audio quality.

The 1400 model proves its worth in numerous functions that are highly practical in your daily business, such as call recording or voice memos. And to customise your phone, you can upload additional ring tones and individual background images.

To find the perfect viewing angle on your desk, simply reposition the feet. And if you prefer to mount it on the wall, it will elegantly hide the wall socket. Incoming calls and messages to your voicemail box are indicated by an LED that is visible all-round.

## Features

### System features

- Calling number and name display (CLIP/CNIP) if registered in the central phone book of the PBX or the telephone
- Automatic detection of S<sub>0</sub> or U<sub>P0</sub> connection
- Automatic background illumination with adjustable brightness and switch-on time
- Individual background images and ring tones
- Ringtone, handset and hands-free speaker volume adjustable
- Microphone mute
- Set-up angle adjustable in 3 steps
- 10 programmable function keys, 2 levels
- Dynamically programmable function keys (8) as touch function in the display
- Power-safe mode
- Power supply via system connection; no additional power supply required
- 1,600 local telephone number entries
- Telephone lock, emergency calls possible
- Desktop and wall mounting
- Access to the central phonebook of the PBX

### Voicemail functions<sup>1</sup>

- Basic activation via the Auerswald Upgrade-Center and start-up with plugging a Micro SD/SDHC card (not included)
- Announcements (25) and messages (250)
- Remote activation and message forwarding
- High-quality audio due to uncompressed recording
- Control via function keys of the telephone
- Total capacity depends on the used memory (1 GB represent approx. 30 h recording capacity)
- Recording and notepad function
- Call acceptance and announcement dependent on type of call (int./ext./door/group)

### Supported Auerswald PBX systems

- COMpact 3000-Serie<sup>2</sup>
- COMpact 4000
- COMpact 2206 USB<sup>3</sup>, 4410 USB<sup>3</sup>
- COMpact 5010 VoIP, 5020 VoIP
- COMpact 5000, 5000R
- COMpact 5200, 5200R
- COMpact 5500R
- COMmander 6000, 6000R, 6000RX
- COMmander Basic.2, Basic.2 19"
- COMmander Business, Business 19"

<sup>1</sup> Activation with costs via the Auerswald Upgrade-Center.

<sup>2</sup> Expansion module for the PBX with one internal S<sub>0</sub> or U<sub>P0</sub> port necessary.

<sup>3</sup> VMC 461.2 managing and firmware updates over ISDN are not supported.

- **Colours:** black
- **Dimensions** (w x h x d): 223 mm x 148/158/168 mm x 185 mm
- **Weight:** approx. 980 g
- **Safety:** CE

## Scope of supply

- COMfortel 1400
- Handset with connection cable
- ISDN cable RJ-45/RJ-45 (approx. 3 m long)
- Installation manual and quick start guide

## Ordering information

- **Product description:** COMfortel 1400, black
- **Article number:** 16069

Copyright © 2018 Auerswald GmbH & Co. KG  
Version 12.0 – Subject to modification

## Technical Data

- **System connection:** S<sub>0</sub>-/U<sub>P0</sub> port
- **Power supply:** via internal S<sub>0</sub> or U<sub>P0</sub> port (PBX)
- **Power consumption:** 1.1 W min., 2 W max.
- **Headset:** separate interface for speaker/microphone sets
- **Display:** TFT colour display (3.5"/8.9 cm, 320 x 240 pixels) with resistive touch
- **LEDs:** 14, some multi coloured
- **Operating elements:** dialling keys with vanity code, 13 function keys, 10 programmable function keys (2 levels)
- **External memory:** Micro SD/SDHC card up to 16 GB, not included
- **Handset:** wideband audio, electret-microphone, dynamical loudspeaker, hearing aid compatible
- **Loudspeaker:** 8 Ohm, Ø 52 mm
- **Hook switch:** magnetically switching contact
- **Case:** plastic